



HotZone® Gas Aisle Series Heaters

Gas HotZone® heaters are high power, high intensity infrared spot heaters that are typically used in groups, with the heaters' beam patterns overlapping in the long dimension, to heat a long thin space. Example: applications include heating a row of workspaces along a conveyor belt, aisles in a warehouse or a bank of checkout stations in a big box store.



Product Number	HZN35120L (natural gas)	HZN70120L (natural gas)	HZN110120L (natural gas)	HZN145120L (natural gas)
	HZL35120L (propane)	HZL70120L (propane)	HZL110120L (propane)	HZL145120L (propane)
Lens Power	3x			
Spot Pattern	2:1 Oval			
Element Type	Ceramic burner			
Typical Mounting Height Range	10' – 18'	13' – 23'	18' – 28'	18' – 28'
≥+15° Spot Size at minimum mounting height*	60 ft ²	120 ft ²	180 ft ²	240 ft ²
Maximum temperature increase at minimum mounting height*	27° F	35° F	27° F	36° F
Maximum temperature increase at maximum mounting height*	11° F	11° F	11° F	15° F
Input Power	35,000 BTU	70,000 BTU	110,000 BTU	145,000 BTU
Gas	Natural gas or propane			
Controller Voltage	120V (24V & mV available)			
Dimensions	32"x14"x23"	32"x21"x23"	32"x28"x23"	32"x34"x23"
Weight	48 lbs.	61 lbs.	75 lbs.	83 lbs.
Standard Colors	Unpainted aluminum			
Color Options	Special order custom colors			
Mounting Options	Ceiling or wall, chain hung			
Other	ETL Certified for vented or unvented use out of direct rain			

*Temperature increase resulting from direct radiant energy. In most applications, surface heating and other affects will also raise the ambient temperature over time and add to the temperature increase.